

## Bitutainer™ Specifications

Suitable for storage and multi-modal transportation of bitumen, bitumen emulsions, polymer modified bitumen's, waste oils and heavy fuel oils.



A unique concept in bitumen distribution with 30% more carrying capacity than conventional tank containers:

- Max capacity 29 000 litres
- Transported as a standard 20ft ISO tank container
- ISO 1496 Part 3 – Type 75 – “Tank Containers”
- Ideal for sea, road and rail transportation
- Design allows partial payloads to be carried (baffled)
- High performance heating systems (8-10°C / hour) via heating tubes (flu pipes)
- High value factory installed insulation with robust outer skin

### Ratings:

Max Gross Weight 35,000 Kgs

Payload 29,000 Kgs

Tare weight is 6,000kgs

### Measurements:

Type	Container Weight			Interior Measurements			Exterior Measurements			Door Opening	
	Gross (KG)	Tare (KG)	Payload (KG)	Length (m)	Width (m)	Height (m)	Capacity (m <sup>3</sup> )	Length (m)	Width (m)	Width (m)	Height (m)
22T1	35,000	6,000	29,000	N/A	N/A	N/A	29,000L	6.058	2.438	N/A	N/A

NOTE: All specifications may vary slightly subject to model and need to be confirmed prior to use.